



> PRINT > COPY > SCAN > FAX

ECOSYS M2035dn
ECOSYS M2535dn

B/W MULTIFUNCTIONALS
FOR A4 FORMAT

THE COMPACT MULTIPURPOSE OFFICE MFP.



These new ECOSYS A4 MFPs have been designed for busy work groups looking for a productive device to support them in their daily office routine. They have a shortened time to first page and produce up to 35 pages per minute when copying or printing. They can also quickly scan and copy double-sided originals with their powerful 50-sheet document processor. These multifunctionals can be complemented with optional paper feeders anytime to meet your needs of today and tomorrow.

- > Up to 35 pages per minute in A4
- > Time to first copy: 6.9 seconds
- > Double-sided print, copy, scan and fax* functionality as standard
- > 50-sheet document processor scans double-sided originals
- > Up to 2 optional paper feeders for up to 800 sheets
- > High security through SSL, IPsec and Private Print** functionality
- > Print from and scan to USB flash drive
- > Exceptionally low printing costs in its class

*Only ECOSYS M2535dn. **Requires additional memory.



ECOSYS stands for ECOlogy, ECONomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that the toner is the only consumable and hardly ever needs to be replaced. The modular design concept allows you to add workflow-enhancing functions as required and the integrated system software provides long-term cross-network compatibility.

GENERAL

Technology: KYOCERA ECOSYS Laser
Control panel display: 5-line LCD display
Engine speed: Up to 35 pages A4 per minute
Resolution: 1,200 dpi quality (1,800 x 600 dpi, print), 600 x 600 dpi, 256 greyscales (scan/copy)
Duty cycle: Max. 50,000 pages per month
Warm-up time: Approx. 20 seconds or less
Time to first print: Approx. 7 seconds or less
Time to first copy: Approx. 6.9 seconds
CPU: PowerPC 465 S/667 MHz
Memory: Standard 512 MB, max. 1,536 MB
Standard interface: USB 2.0 (Hi-Speed), USB Host (High Speed), 10 Base-T/100 Base-TX/1000 Base-T, slot for optional SD card, slot for optional print server (ECOSYS M2035dn only)
Integrated accounting: 100 department codes
Dimensions (W x D x H): 494 x 430 x 448 mm
Weight: Approx. 18 kg
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption: ECOSYS M2035dn/M2535dn
 Copying/Printing: 439 W
 Ready mode: 65 W
 Sleep mode: 3.7 W
 Plug-in off mode: 0.3 W or less
Noise (sound pressure level ISO 7779/ISO 9296):
ECOSYS M2035dn/M2535dn:
 Copying/Printing: Half-speed mode 49 dB(A) LpA
 Copying/Printing: Full-speed mode 51.5/51.3 dB(A) LpA
 Standby (Ready-mode): 27.6/27.5 dB(A) LpA
Safety standards: TÜV/GS, CE
 This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.
Input capacity: 50-sheet multi-purpose tray, 60 – 220 g/m², A4, A5, A6, B5, Letter, Legal, Folio, envelopes, Custom (70 x 148 to 216 x 356 mm) 250-sheet universal paper cassette, 60 – 120 g/m², A4, A5, A6, B5, Letter, Legal, Folio, Custom (105 x 148 to 216 x 356 mm)
Max. input capacity with options: 800 sheets
Duplex unit: Duplex as standard supports 60 – 105 g/m²
 Reversing document processor: 50-sheet, simplex scan 50 – 120 g/m², duplex scan 50 – 110 g/m², A4, A5, B5, Letter, Legal, Custom (140 x 210 to 216 x 356 mm)

Output capacity: Max. 150 sheets face-down

PRINT FUNCTIONS

Controller language: PRESCRIBE IIe
Emulations: PCL6 (5c/XL), KPDL 3 (PostScript 3-compatible), Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF Direct Print Vers. 1.7, XPS Direct Print (requires memory expansion)
Operating systems: All current Windows operating systems, MAC OS X version 10.4 or higher, Unix, Linux as well as other operating systems on request
Fonts/barcodes: 93 outline fonts (PCL 6, HP-compatible) + 8 (Windows Vista), 101 (KPDL3), 1 bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)
Features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3 and Private Print (requires memory expansion), IPPS, HTTPS, POP over SSL, AirPrint, SMT over SSL, FTP over SSL, LDAP over SSL

COPY FUNCTIONS

Max. original size: A4/Legal
Continuous copying: 1 – 999
Zoom range: 25 – 400% in 1% steps
Preset magnification ratios: 7 Reductions/5 Enlargements
Exposure mode: Auto, manual: 5 steps
Image adjustments: Text + photo, text, photo
Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change, copy density control

SCAN FUNCTIONS

Functionality: Scan-to-e-mail, Scan-to-FTP (FTP over SSL), Scanto SMB, Scan to USB Host, TWAIN (USB), WSD (WIA) scan (USB)
Scan speed: 35 ipm (300 dpi, A4, b/w), 14 ipm (300 dpi, A4, colour)
Scan resolution: 600, 400, 300, 200 dpi (256 greyscales)
Max. scan size: A4, Legal
Original recognition: Text, photo, text + photo, for OCR
File types: TIFF, PDF, JPEG, XPS, PDF/A
Compression method: MMR/JPEG
Features: Colour scan, integrated address book, Active Directory support, encrypted data transfer, multi-send (e-mail, fax, SMB/FTP folder, print) at once

COMMAND CENTER RX

The Command Centre RX enables to control and manage various settings by accessing the device via a common web browser. It automatically updates screens, customises user screens, and displays department and restriction settings.

USB INTERFACE FOR USB FLASH MEMORY DEVICE

Documents can be printed directly from a USB flash memory device via the USB host interface. You can select documents stored as PDF, XPS, TIFF or JPEG directly on the printer's control panel. No computer is required.

FAX FUNCTIONS (ECOSYS M2535DN ONLY)

Compatibility: ITU-T Super G3
Modem speed: Max. 33.6 kbps
Transmission speed: Less than 3 seconds
Scanning speed: 2.5 seconds
One-touch dial: 22 numbers
Address book: 200 entries
Maximum original size: A4, Legal
Compression method: JBIG, MMR, MR, MH
Memory reception: 256 sheets or more
Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast, memory reception

OPTIONS

Paper handling:
PF-120 Paper feeder: Max. 250 sheets, 60–120 g/m², A4, A5, B5, Letter, Legal, Custom (148 x 210 mm to 216 x 297 mm)
Memory: MDDR3-1GB (DDR3)
USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available
Optional interfaces (ECOSYS M2035dn only):
IB-50: Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ-45)
IB-51: Wireless LAN (802.11b/g/n)
CB-120: Wooden desk with storage capacity, including castors (wheels)

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19752
TK-1140 Toner-Kit: Microfine toner for 7,200 pages A4
 Capacity of starter toner is 3,600 pages A4

WARRANTY

2-year carry-in warranty as standard. KYOCERA guarantees the drum and developer for 3 years or 100,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.



KYOCERA Document Solutions Belgium – Sint-Martinusweg 199-201 – 1930 Zaventem
 Tel +32 (0)2 720 92 70 - www.kyoceradocumentsolutions.be

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

YOUR KYOCERA PARTNER

